

### Longpass Glass Absorption Filter Sets

We offer four sets of technical grade longpass absorption filters covering the UV to NIR spectral range. These filters transmit more than 80% of the light at 0° AOI and have no AR coating. These sets enable tailoring the passband to a specific machine vision application. Unlike interference filters, these filters enable large FOV, and are used to enhance contrast when the blue-shift effect is a problem. The filters can be supplied as round windows with a 12.5mm or 25mm diameter, or as 50mmX50mm square windows. There are four types of sets:

**UV** - 9 longpass filters 2mm thick: 220,240,260,280,300,320,340,360,380 nm.

**LVR** - 10 longpass filters 2mm thick: 400,420,450,470,490,510,535,550,565,580 nm

**TVR** - 9 longpass filters 2mm thick: 600,610,630,640,650,670,685,700,720 nm

**NIR** - 5 longpass filters 3mm thick: 760,780,800,830,850 nm

<p><b>Top Visible Range Cut-On Absorption filter set</b>            9 longpass glass filters in the 600-720nm spectral range            Thickness: 2mm            Round - 12.5\25mm Diameter or Square - 50mmX50mm            50% cut-on [nm]: 600,610,630,640,650,670,685,700,720</p>		<p><u>Specific Tolerances:</u>            Cut-on slope [%T/nm]: 1.5 - 2.2            50% cut-on [nm]: +/-10            Max. Transmittance: &gt; 80%  <u>General Tolerances:</u>            Thickness [mm]: +/- 0.05            Outer dimensions [mm]: +0.0/-0.1            Parallelism [arcmin]: &lt;5            Finish (S-D): 60-40            Flatness: 1/4 Lambda</p>
CSTM P/N	Description	
FS-TVRCO-12.5D-G	12.5mm Dia. X 2mm Thick - 9 longpass filters covering the 600-720nm spectral range	
FS-TVRCO-25D-G	25mm Dia. X 2mm Thick - 9 longpass filters covering the 600-720nm spectral range	
FS-TVRCO-50S-G	50mm X 50mm X 2mm Thick - 9 longpass filters covering the 600-720nm spectral range	

